GECKO HARD WAX CARNAUBA

Page: 1

Compilation date: 12/01/2015

Revision date: 23/10/19

**Revision No: 4** 

### Section 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name: Gecko Hard wax carnauba

**Product code:** 687601 - 150 ML

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company name: Maumo International B.V.

P.O. Box 441

2990 AK Barendrecht

Tel: +31 (0) 180 699 234 Fax: +31 (0) 180 699 235

Email: Info@maumo.nl

### 1.4. Emergency telephone number

### **Emergency tel:**

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking.

### 2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

#### 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

# 3.2. Mixtures

#### GECKO HARD WAX CARNAUBA

Page: 2

[cont...]

#### Hazardous ingredients:

#### DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	Asp. Tox. 1: H304; -: EUH066	50-70%

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

## 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

# 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

## 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

#### GECKO HARD WAX CARNAUBA

Page: 3

Clean-up procedures: Wash the spillage site with large amounts of water.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Avoid the formation or spread of dust in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

## **Hazardous ingredients:**

# DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Workplace exposure limits:

	Res	pirabl	le d	lust
--	-----	--------	------	------

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
EU			1200 MG/M3	-	
	-	-			

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Not applicable.

Respiratory protection: Respiratory protective device with particle

filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Not applicable.

# Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Solid

Colour: Pale green
Odour: Pleasant

Evaporation rate: Negligible

#### GECKO HARD WAX CARNAUBA

Page: 4

Oxidising: Not applicable.

Solubility in water: Insoluble

Also soluble in: hydrocarbons

Viscosity: Not applicable.

Boiling point/range°C: >35 Melting point/range°C: No data available.

Flammability limits %: lower: Not applicable. upper: No data available.

Flash point°C: 60 - 93 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.8 pH: 7

VOC g/I: No data available.

#### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

## 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# Section 11: Toxicological information

### 11.1. Information on toxicological effects

## **Hazardous ingredients:**

#### DISTILLATES (PETROLEUM). HYDROTREATED LIGHT

SIGNIED (1 ETROLLOM), TIDICO TREATED LIGHT				
DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/l

Toxicity values: No data available.

#### GECKO HARD WAX CARNAUBA

Page: 5

#### Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

#### Hazardous ingredients:

## DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

ALGAE	72H IC50	20	ppm
Daphnia magna	48H EC50	>1000	mg/l
FISH	96H LC50	>1000	ppm
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>250	ppm

### 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Not applicable. Recovery

operations: Not applicable.

**Disposal of packaging:** Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

## Section 14: Transport information

Transport class: This product does not require a classification for transport.

#### GECKO HARD WAX CARNAUBA

Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and

shall be used only as a guide. This company shall not be held liable for any damage resulting

from handling or from contact with the above product.

Page: 6

GECKO HARD WAX CARNAUBA

Page: 7 [final page]