




D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** D-CON WHEEL & RIM WAX V2 - D_10100_2
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Polishing and protective wax
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Autodetailing EU
Klavermaten 26
7472DD Goor - Overijssel - Netherlands
Phone: +31 (0) 546 456 716
info@carcare24.eu
www.carcare24.eu
Phone Number: +31 (0) 546 456 716
IMPORT
- 1.4 Emergency telephone number:** Chemtrec: (800)424-9300 (24/h)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning

Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P264: Wash hands thoroughly after handling
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/face protection.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical advice/attention.
P501: Dispose of contents/container according to the separated collection system used in your municipality.
Supplementary information:
EUH066: Repeated exposure may cause skin dryness or cracking.
EUH208: Contains 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
UFI: M2Q3-00G6-F00P-3CNE
- 2.3 Other hazards:**
Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- CONTINUED ON NEXT PAGE -













D-CON WHEEL & RIM WAX V2 - D_10100_2
SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)
3.1 Substance:

Non-applicable

3.2 Mixture:
Chemical description: Wax/es

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics ¹	Self-classified	15 - <30 %
	Asp. Tox. 1: H304; EUH066 - Danger		
CAS: Non-applicable EC: 945-969-9 Index: Non-applicable REACH: Non-applicable	Hexadecyl-aminoethylaminopropyl-polydimethylsiloxane ¹	Self-classified	5 - <10 %
	Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger		
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	Ethyl acetate ²	ATP CLP00	0,1 - <1 %
	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	 	
CAS: 541-02-6 EC: 208-764-9 Index: Non-applicable REACH: 01-2119511367-43-XXXX	Decamethylcyclopentasiloxane ³	Not classified	0,1 - <1 %
CAS: 123-92-2 EC: 204-662-3 Index: 607-130-00-2 REACH: 01-2119548408-32-XXXX	Isopentyl acetate ²	ATP CLP00	<0,1 %
	Flam. Liq. 3: H226; EUH066 - Warning		
CAS: 431-03-8 EC: 207-069-8 Index: Non-applicable REACH: 01-2120772074-56-XXXX	Butanedione ²	Self-classified	<0,1 %
	Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	  	
CAS: 2682-20-4 EC: 220-239-6 Index: Non-applicable REACH: 01-2120764690-50-XXXX	2-methyl-2H-isothiazol-3-one ¹	Self-classified	<0,1 %
	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger	  	

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

² Substance with a Union workplace exposure limit

³ PBT/vPvB substance

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

2-methyl-2H-isothiazol-3-one	10
CAS: 2682-20-4 EC: 220-239-6	1

SECTION 4: FIRST AID MEASURES
4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

- CONTINUED ON NEXT PAGE -



D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 4: FIRST AID MEASURES (continued)

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

- CONTINUED ON NEXT PAGE -



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Ethyl acetate CAS: 141-78-6 EC: 205-500-4	200 ppm	734 mg/m ³
	400 ppm	1468 mg/m ³
Isopentyl acetate CAS: 123-92-2 EC: 204-662-3	50 ppm	270 mg/m ³
	100 ppm	540 mg/m ³
Butanedione CAS: 431-03-8 EC: 207-069-8	0,02 ppm	0,07 mg/m ³
	0,1 ppm	0,36 mg/m ³

DNEL (Workers):

Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Decamethylcyclopentasiloxane CAS: 541-02-6 EC: 208-764-9	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	1468 mg/m ³	1468 mg/m ³	734 mg/m ³	734 mg/m ³
	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Non-applicable	Non-applicable	97,3 mg/m ³	24,2 mg/m ³

- CONTINUED ON NEXT PAGE -


D-CON WHEEL & RIM WAX V2 - D_10100_2
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

2-methyl-2H-isothiazol-3-one

CAS: 2682-20-4

EC: 220-239-6

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

0,043 mg/m³

Non-applicable

0,021 mg/m³

DNEL (General population):

Ethyl acetate

CAS: 141-78-6

EC: 205-500-4

Non-applicable

Non-applicable

4,5 mg/kg

Non-applicable

Non-applicable

Non-applicable

37 mg/kg

Non-applicable

734 mg/m³

734 mg/m³

367 mg/m³

367 mg/m³

Decamethylcyclopentasiloxane

CAS: 541-02-6

EC: 208-764-9

Non-applicable

Non-applicable

5 mg/kg

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

17,3 mg/m³

4,3 mg/m³

4,3 mg/m³

2-methyl-2H-isothiazol-3-one

CAS: 2682-20-4

EC: 220-239-6

0,053 mg/kg

Non-applicable

0,027 mg/kg

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

Non-applicable

0,043 mg/m³

Non-applicable

0,021 mg/m³

PNEC:

Ethyl acetate

CAS: 141-78-6

EC: 205-500-4

650 mg/L

0,24 mg/L

0,148 mg/kg

0,024 mg/L

1,65 mg/L

1,15 mg/kg

0,2 g/kg

0,115 mg/kg

Decamethylcyclopentasiloxane

CAS: 541-02-6

EC: 208-764-9

10 mg/L

0,0012 mg/L

2,54 mg/kg

0,00012 mg/L

Non-applicable

11 mg/kg

0,016 g/kg

1,1 mg/kg

Isopentyl acetate

CAS: 123-92-2

EC: 204-662-3

30 mg/L

0,011 mg/L

0,06 mg/kg

0,001 mg/L

0,11 mg/L

0,335 mg/kg

Non-applicable

0,034 mg/kg

2-methyl-2H-isothiazol-3-one

CAS: 2682-20-4

EC: 220-239-6

0,23 mg/L

0,00339 mg/L

0,047 mg/kg

0,00339 mg/L

0,00339 mg/L

Non-applicable

Non-applicable

Non-applicable

8.2 Exposure controls:
A.- Individual protection measures, such as personal protective equipment

As a preventive measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.



C.- Specific protection for the hands

 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.
--	--	---	-------------------	--





As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

- CONTINUED ON NEXT PAGE -




D-CON WHEEL & RIM WAX V2 - D_10100_2
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)
D.- Eye and face protection

	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
---	-------------	---	---	---

E.- Body protection

	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 EN 168:2002 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
	Safety footwear for protection against chemical risk		EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011		DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
--	---	---	--

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	31,73 % weight
V.O.C. density at 20 °C:	308,08 kg/m ³ (308,08 g/L)
Average carbon number:	11,82
Average molecular weight:	138,37 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	 Lavender
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	121 °C
Vapour pressure at 20 °C:	2209 Pa
Vapour pressure at 50 °C:	11600,08 Pa (11,6 kPa)
Evaporation rate at 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Product description:

Density at 20 °C:	971 kg/m ³
Relative density at 20 °C:	0,971
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	~8
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	>63 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	265 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

- CONTINUED ON NEXT PAGE -


D-CON WHEEL & RIM WAX V2 - D_10100_2
SECTION 10: STABILITY AND REACTIVITY (continued)

Not applicable	Not applicable	Precaution	Precaution	Not applicable
----------------	----------------	------------	------------	----------------

10.5 Incompatible materials:

Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases
--------------------	----------------	---------------------	----------------	-------------------------------

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION
11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Poly(tetrafluoroethylene) (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -



D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Other information:

Non-applicable

Specific toxicology information on the substances:

Ethyl acetate	4100 mg/kg	Rat
CAS: 141-78-6	20000 mg/kg	Rabbit
EC: 205-500-4	Non-applicable	
Isopentyl acetate	7400 mg/kg	Rat
CAS: 123-92-2	Non-applicable	
EC: 204-662-3	Non-applicable	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Ethyl acetate	230 mg/L (96 h)	Pimephales promelas	Fish
CAS: 141-78-6	717 mg/L (48 h)	Daphnia magna	Crustacean
EC: 205-500-4	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
Isopentyl acetate	Non-applicable		
CAS: 123-92-2	42 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-662-3	Non-applicable		
2-methyl-2H-isothiazol-3-one	4,77 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2682-20-4	0,932 mg/L (48 h)	Daphnia magna	Crustacean
EC: 220-239-6	0,063 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Ethyl acetate	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	2,4 mg/L	Daphnia magna	Crustacean
2-methyl-2H-isothiazol-3-one	4,93 mg/L	Oncorhynchus mykiss	Fish
CAS: 2682-20-4 EC: 220-239-6	0,044 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Ethyl acetate	1,36 g O2/g	100 mg/L
CAS: 141-78-6	1,69 g O2/g	14 days
EC: 205-500-4	0,8	83 %
2-methyl-2H-isothiazol-3-one	Non-applicable	10 mg/L
CAS: 2682-20-4	Non-applicable	28 days
EC: 220-239-6	Non-applicable	55,8 %

12.3 Bioaccumulative potential:

Substance-specific information:

- CONTINUED ON NEXT PAGE -


D-CON WHEEL & RIM WAX V2 - D_10100_2
SECTION 12: ECOLOGICAL INFORMATION (continued)

Ethyl acetate	30
CAS: 141-78-6	0.73
EC: 205-500-4	Moderate
Isopentyl acetate	10
CAS: 123-92-2	
EC: 204-662-3	Low
2-methyl-2H-isothiazol-3-one	
CAS: 2682-20-4	-0.49
EC: 220-239-6	

12.4 Mobility in soil:

Ethyl acetate	59	13,58 Pa·m ³ /mol
CAS: 141-78-6	Very High	Yes
EC: 205-500-4	2,324E-2 N/m (25 °C)	Yes
Isopentyl acetate	70	59,78 Pa·m ³ /mol
CAS: 123-92-2	Very High	Non-applicable
EC: 204-662-3	2,388E-2 N/m (25 °C)	Yes
2-methyl-2H-isothiazol-3-one	Non-applicable	0E+0 Pa·m ³ /mol
CAS: 2682-20-4	Non-applicable	Non-applicable
EC: 220-239-6	Non-applicable	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Decamethylcyclopentasiloxane

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS
13.1 Waste treatment methods:

20 01 29*	detergents containing hazardous substances	Dangerous
-----------	--	-----------

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

- CONTINUED ON NEXT PAGE -



D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-methyl-2H-isothiazol-3-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Decamethylcyclopentasiloxane

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 2-methyl-2H-isothiazol-3-one (Product-type 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc)

:

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Other information:

The information contained herein is based on data considered to be accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



D-CON WHEEL & RIM WAX V2 - D_10100_2

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 2: H330 - Fatal if inhaled.
 Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.
 Acute Tox. 4: H302 - Harmful if swallowed.
 Aquatic Acute 1: H400 - Very toxic to aquatic life.
 Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
 Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
 Eye Dam. 1: H318 - Causes serious eye damage.
 Eye Irrit. 2: H319 - Causes serious eye irritation.
 Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
 Flam. Liq. 3: H226 - Flammable liquid and vapour.
 Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
 Skin Irrit. 2: H315 - Causes skin irritation.
 Skin Sens. 1: H317 - May cause an allergic skin reaction.
 Skin Sens. 1A: H317 - May cause an allergic skin reaction.
 STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -